

Press jaws for HVACR are proprietary to each fitting brand - unlike those for other systems, which are universal.



Press Tools for Streamline® ACR Copper Press Fittings

The following full-sized press tools with axial thrust 32-34kN are suitable:

- Milwaukee® M18™ FORCE LOGIC™ 2922-20
- Milwaukee® M18™ Long Throw 2773-20L
- Ridgid® RP300 series 320-E, RP 330-B, RP 330-C, or RP 340, RP 350
- Dewalt® Full Sized DCE200M2
- REMS Full Sized 579011, 579010, 571014, 576011, 576010, 577010, 57211
- Hilti Full Sized NPR 32-A Pipe Press Tool
- Klauke® UAP Series
- Rothenberger ROMAX® 4000, 3000, & AC ECO Series

Press Jaws for Streamline® ACR Copper Press Fittings

Milwaukee® Tool has developed jaws for use specifically with Streamline® ACR Copper Press Fittings.

Jaw kits are available with and without a Press Tool.

- 1/4" Milwaukee® Streamline® ACR Press Jaw (49-16-2650M)
- 3/8" Milwaukee® Streamline® ACR Press Jaw (49-16-2652M)
- 1/2" Milwaukee® Streamline® ACR Press Jaw (49-16-2653M)
- 5/8" Milwaukee® Streamline® ACR Press Jaw (49-16-2654M)
- 3/4" Milwaukee® Streamline® ACR Press Jaw (49-16-2655M)
- 7/8" Milwaukee® Streamline® ACR Press Jaw (49-16-2656M)
- 1-1/8" Milwaukee® Streamline® ACR Press Ring (49-16-2657M)
- Milwaukee® FORCE LOGIC™ Ring Jaw (also needed for 1-1/8") (49-16-2659)

**1/4" - 7/8"
Milwaukee® Streamline®
ACR Press Jaws**



**1-1/8" +
ACR Press Jaw & Ring
(Both Required)**



**C
COPPER**

**PR
PRESS**

**H
HVAC/R**