

BALL VALVES, GAS VALVES & PLUMBING VALVES

VLV 0822
Effective Aug 22, 2022
 (Supersedes UW VLV0622)

The issuance of this price list is not an offer to sell the goods listed herein at the prices stated.

BALL VALVES • BRASS



SERIES 7690MF Lead Free Brass Ball Valve

 Full port, Brass, PEX F1960
 connection MIP x Barbed

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
107-321NL	1/4	MIP x MIP	20	200	0.15	16.62

Features:

- 500 PSI WOG
- -20°F to 350°F temperature range
- Suitable for vacuum use up to 7 PSI



SERIES 7690CMP Lead Free Brass Ball Valve

Brass, compression connection

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
107-023NL	1/2	OD x OD	-	12	0.50	27.57
107-024NL	3/4	OD x OD	-	12	0.75	46.65
107-025NL	1	OD x OD	6	24	1.10	71.27

Features:

- 200 PSI WOG
- -20°F to 350°F temperature range
- Suitable for vacuum use up to 7 PSI
- Compression ends for solderless connection to copper tubing



SERIES 7690PF Lead Free Brass Ball Valve

 Full port, forged brass, packing
 gland, push fit

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
1107-063	1/2	PF x PF	25	100	0.39	18.54
1107-064	3/4	PF x PF	15	60	0.59	26.24
1107-065	1	PF x PF	15	60	0.98	43.27

Features:

- 200 PSI WOG
- 200 PSI @ 200°F
- Full port for maximum flow rate
- Packing Gland - blowout proof stem design
- PTFE seat & packing
- Rust-resistant heavy-duty handle with vinyl grip
- Dezincification-resistant lead-free brass construction
- Chrome-plated brass ball & stem
- 316 stainless steel grip ring for strength and corrosion resistance
- Integrated brass seal gland increases durability & work life
- Compatible with Copper, CPVC & PEX tubing
- PEX stiffeners included with each fitting
- Removable with use of disconnect clip



BALL VALVES • PLASTIC



SERIES 6700WT

PVC Ball Valve

Full port, IPS, white, Schedule 40

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
107-133	1/2	FIP x FIP	10	100	0.22	3.48
107-134	3/4	FIP x FIP	5	60	0.30	4.38
107-135	1	FIP x FIP	5	40	0.54	6.98
107-136	1-1/4	FIP x FIP	5	30	0.63	9.94
107-137	1-1/2	FIP x FIP	4	24	0.91	14.54
107-138	2	FIP x FIP	2	16	1.49	22.30
107-139	2-1/2	FIP x FIP	-	12	3.15	63.84
107-140	3	FIP x FIP	-	6	4.01	110.13
107-141	4	FIP x FIP	-	4	7.50	199.63

Features:

- 150 PSI @ 73°F
- Fits schedule 40 & 80 pipe
- Quarter turn operation
- TPV seats & EPDM O-rings
- Large ports for maximum flow rates
- Designed for use in residential, commercial and industrial fluid systems as well as wastewater, chemical and agricultural applications
- For use with cold-water applications



SERIES 6700WS

PVC Ball Valve

Full port, solvent, white, Schedule 40

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
107-633	1/2	SLIP x SLIP	10	100	0.21	3.48
107-634	3/4	SLIP x SLIP	5	60	0.25	4.38
107-635	1	SLIP x SLIP	5	40	0.37	6.98
107-636	1-1/4	SLIP x SLIP	5	30	0.54	9.94
107-637	1-1/2	SLIP x SLIP	4	24	0.84	14.54
107-638	2	SLIP x SLIP	2	16	1.43	22.30
107-639	2-1/2	SLIP x SLIP	-	12	2.76	63.84
107-640	3	SLIP x SLIP	-	6	3.80	110.13
107-641	4	SLIP x SLIP	-	4	7.05	199.63

Features:

- 150 PSI @ 73°F
- Fits schedule 40 pipe
- Quarter turn operation
- TPV seats & EPDM O-rings
- Large ports for maximum flow rates
- Designed for use in residential, commercial and industrial fluid systems as well as wastewater, chemical and agricultural applications
- For use with cold-water applications



SERIES 6700GT

PVC Ball Valve

Full port, IPS, grey, Schedule 80

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
107-103	1/2	FIP x FIP	10	100	0.17	7.06
107-104	3/4	FIP x FIP	5	60	0.26	9.11
107-105	1	FIP x FIP	5	40	0.41	12.97
107-106	1-1/4	FIP x FIP	5	30	0.57	21.12
107-107	1-1/2	FIP x FIP	4	24	0.86	28.29
107-108	2	FIP x FIP	2	16	1.46	42.63

Features:

- 150 PSI @ 73°F
- PTFE seats
- Fits both Schedule 40 & 80 pipe
- EPDM O-ring



SERIES 6700GS

PVC Ball Valve

Full port, solvent, grey, Schedule 80

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
107-603	1/2	SLIP x SLIP	10	100	0.16	7.06
107-604	3/4	SLIP x SLIP	5	60	0.24	9.11
107-605	1	SLIP x SLIP	5	40	0.39	12.97
107-606	1-1/4	SLIP x SLIP	5	30	0.54	21.12
107-607	1-1/2	SLIP x SLIP	4	24	0.81	28.29
107-608	2	SLIP x SLIP	2	16	1.40	42.62

Features:

- 150 PSI @ 73°F
- PTFE seats
- Fits both Schedule 40 & 80 pipe
- EPDM O-ring



SERIES 6700CTS

CPVC Ball Valve

Full port, solvent, white, Schedule 40

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
107-123	1/2	SLIP x SLIP	10	100	0.11	5.82
107-124	3/4	SLIP x SLIP	5	60	0.18	8.96
107-125	1	SLIP x SLIP	5	40	0.28	13.73
107-126	1-1/4	SLIP x SLIP	5	40	0.63	28.18
107-127	1-1/2	SLIP x SLIP	5	30	0.60	42.23
107-128	2	SLIP x SLIP	4	24	1.60	56.22

Features:

- 100 PSI @ 180°F
- For use with hot or cold water
- Teflon seats
- For use with CPVC/copper tube size pipe
- EPDM O-rings
- Quarter turn operations
- Large ports for maximum flow rates



GAS VALVES



SERIES 7701G

Gas Ball Valve

Forged brass, one piece body,
lever handle

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
110-522	3/8	FIP x FIP	10	100	0.31	17.40
110-523	1/2	FIP x FIP	10	100	0.38	17.40
110-524	3/4	FIP x FIP	10	100	0.57	25.70

Features:

- 200 PSI
- 1/2 PSIG and 5G certified
- -20°F to 300°F temperature range
- Quarter-turn lever handle for positive on/off operation
- Coated aluminum handle for corrosion and solvent resistance
- Multi-directional flow
- One-piece body for leak resistance and long valve life
- Chrome plated brass ball



SERIES 7701GST

Gas Ball Valve

Forged brass, one piece body,
side tap

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
110-553	1/2	FIP x FIP	10	100	0.42	29.13
110-554	3/4	FIP x FIP	10	100	0.61	38.37
110-555	1	FIP x FIP	6	30	1.11	70.44

Features:

- 200 PSI
- 1/2 PSIG and 5G certified
- -10°F to 300°F temperature range
- Quarter-turn lever handle for positive on/off operation
- Coated aluminum handle for corrosion and solvent resistance
- Multi-directional flow
- One-piece body for leak resistance and long valve life
- Chrome plated brass ball



SERIES 7701GFL

Gas Ball Valve

Forged brass, one piece body

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
116-502	3/8	FL x FL	10	100	0.37	26.12
116-503	1/2	FL x FL	10	100	0.34	26.11
116-504	5/8	FL x FL	10	100	0.52	37.25

Features:

- 200 PSI
- 1/2 PSIG and 5G certified
- -20°F to 300°F temperature range
- Chrome plated brass ball
- Coated aluminum handle for corrosion and solvent resistance
- One-piece body for leak resistance and long valve life



SERIES 7701GFLM

Gas Ball Valve

Forged brass, one piece body

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
116-512	3/8 x 1/2	FL x MIP	10	100	0.33	31.50
116-513	1/2 x 1/2	FL x MIP	10	100	0.35	32.00

Features:

- 200 PSI
- 1/2 PSIG and 5G certified
- -20°F to 300°F temperature range
- Chrome plated brass ball
- Coated aluminum handle for corrosion and solvent resistance
- One-piece body for leak resistance and long valve life



SERIES 7701GFLF

Gas Ball Valve - Straight

Forged brass, one piece body

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
114-522	3/8 x 1/2	FL x FIP, Straight	10	100	0.34	22.37
114-523	1/2	FL x FIP, Straight	10	100	0.35	22.35
114-544	1/2 x 3/4	FL x FIP, Straight	10	100	0.41	35.31
114-543	15/16 x 1/2	FL x FIP, Straight	10	100	0.35	32.78
114-524	15/16 x 3/4	FL x FIP, Straight	10	100	0.57	35.21

Features:

- 200 PSI
- 1/2 PSIG and 5G certified
- -20°F to 300°F temperature range
- Chrome plated brass ball
- Coated aluminum handle for corrosion and solvent resistance
- One-piece body for leak resistance and long valve life



SERIES 7701GSTF

Gas Ball Valve - Angle

Forged brass, one piece body

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
114-533	3/8 x 1/2	FL x FIP, Angle	10	100	0.33	35.20
114-534	15/16 x 3/4	FL x FIP, Angle	10	100	0.58	46.71

Features:

- 200 PSI
- 1/2 PSIG and 5G certified
- -20°F to 300°F temperature range
- Chrome plated brass ball
- Coated aluminum handle for corrosion and solvent resistance
- One-piece body for leak resistance and long valve life



GAS VALVES / LOG LIGHTER



SERIES 7701GSTF Gas Ball Valve - Side Tap

Forged brass, one piece body

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
116-552	3/8	FL x FL & Side Tap	10	100	0.41	33.32
116-553	1/2	FL x FL & Side Tap	10	100	0.39	33.32

Features:

- 200 PSI
- 1/2 PSIG and 5G certified
- -20°F to 300°F temperature range
- Chrome plated brass ball
- Coated aluminum handle for corrosion and solvent resistance
- One-piece body for leak resistance and long valve life



SERIES 7701GHV Gas Heater Valve

For 3/8" tube

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
117-592	9/16 - 24 x 1/2	Fine Thread FL	10	100	0.33	24.07

Features:

- 200 PSI
- 1/2 PSIG and 5G certified
- -20°F to 300°F temperature range
- 9/16 - 24 Fine Flare Thread for 3/8" tubing
- One-piece body for leak resistance and long valve life
- Chrome plated brass ball
- Coated aluminum lever handle for corrosion resistance



SERIES 7701GTX Gas Cock - Texas Pattern

Forged brass

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
115-503	1/2 (1/2 x 1/8)	FIP - MIP	10	100	0.35	36.00

Features:

- 200 PSI
- 1/2 PSIG and 5G certified
- -20°F to 300°F temperature range
- Texas pattern
- For use with water up to 175 PSI
- One-piece body for leak resistance and long valve life
- Chrome plated brass ball
- Coated aluminum lever handle



SERIES 7702G Gas Ball Valve

Forged brass, two piece body, lever handle

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
110-122	3/8	FIP x FIP	10	100	0.28	18.78
110-123HC	1/2	FIP x FIP	-	20	0.34	18.78
110-124HC	3/4	FIP x FIP	-	10	0.53	23.21
110-125	1	FIP x FIP	6	30	0.84	55.81

Features:

- 200 PSI
- 1/2 PSIG and 5G certified
- -20°F to 300°F temperature range
- Quarter turn lever handle for positive on/off operation
- Coated aluminum handle for corrosion & solvent resistance
- Multi-directional flow
- Two-piece body design
- Chrome plated brass ball



SERIES 7702GE Gas Ball Valve

Forged brass, two piece body, lever handle

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
110-222	3/8	FIP x FIP	10	100	0.27	12.42
110-223C	1/2	FIP x FIP	10	100	0.33	12.42
110-223HC	1/2	FIP x FIP	-	30	0.33	12.42
110-223R	1/2	FIP x FIP	10	100	0.33	12.42
110-224C	3/4	FIP x FIP	10	100	0.48	20.08
110-224HC	3/4	FIP x FIP	-	20	0.48	20.08
110-225	1	FIP x FIP	6	36	0.91	31.40

Features:

- 175 PSI
- 1/2 PSIG and 5G certified
- -20°F to 300°F temperature range
- Quarter turn lever handle for positive on/off operation
- Coated aluminum handle for corrosion & solvent resistance
- Multi-directional flow
- Two-piece body design
- Chrome plated brass ball



GAS VALVES • LOG LIGHTER



SERIES 7702GLLC Log Lighter Valve

with key

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
118-001	1/2	Straight, Chrome	-	25	0.75	55.97
118-002	1/2	Angle, Chrome	-	25	0.75	56.01
118-003	1/2	Straight, Polished Brass	-	25	0.75	61.33
118-004	1/2	Angle, Polished Brass	-	25	0.75	61.36

Features:

- 158,000 BTU for 118-001 & 118-003
- 98,000 BTU for 118-002 & 118-004
- 1/2 PSIG and 5G
- Decorative polished-brass face plate & key
- Adjustable height flange
- Includes the key



PLUMBING VALVES • LOW PRESSURE • GATE VALVES



Gate Valve

Brass, screw over bonnet, heavy duty

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
100-202NL	3/8	FIP x FIP	10	100	0.55	26.91
100-203NL	1/2	FIP x FIP	10	100	0.80	41.00
100-204NL	3/4	FIP x FIP	5	60	1.10	53.52
100-205NL	1	FIP x FIP	5	40	1.74	75.74
100-206NL	1-1/4	FIP x FIP	5	30	2.40	124.43
100-207NL	1-1/2	FIP x FIP	4	20	3.14	152.16
100-208	2	FIP x FIP	2	16	4.76	311.46

Features:

- 300 PSI WOG / 150 PSI WSP
- Full port for maximum flow rate
- Non-rising stem for limited-space operation
- Screw over bonnet for extra strength
- Heavy brass construction for quality and dependability
- Solid wedge disc



Gate Valve

Brass, screw over bonnet, heavy duty

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
100-703NL	1/2	SWT x SWT	10	100	0.72	41.01
100-704NL	3/4	SWT x SWT	5	60	1.04	53.51
100-705NL	1	SWT x SWT	5	40	1.44	75.76

Features:

- 300 PSI WOG / 150 PSI WSP
- Full port for maximum flow rate
- Non-rising stem for limited-space operation
- Screw over bonnet for extra strength
- Heavy brass construction for quality and dependability
- Solid wedge disc



Gate Valve

Forged brass, non-rising stem, heavy duty

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
100-001NL	1/4	FIP x FIP	10	100	0.60	21.92
100-002NL	3/8	FIP x FIP	10	100	0.60	21.92
100-003NL	1/2	FIP x FIP	10	100	0.57	21.92
100-004NL	3/4	FIP x FIP	5	60	0.71	28.92
100-005NL	1	FIP x FIP	5	40	1.13	45.06
100-006NL	1-1/4	FIP x FIP	5	30	1.65	63.11
100-007NL	1-1/2	FIP x FIP	4	24	2.15	86.66
100-008	2	FIP x FIP	2	16	3.50	120.62
100-008NL	2	FIP x FIP	2	16	3.35	134.61
100-009	2-1/2	FIP x FIP	2	8	6.40	179.67
100-010	3	FIP x FIP	1	6	8.90	217.07
100-011	4	FIP x FIP	-	3	14.05	418.92

Features:

- 200 PSI WOG / 125 PSI WSP
- Full port for maximum flow rate
- Non-rising stem for limited-space operation
- Six point cast-iron handle
- Forged brass construction for quality and dependability
- Brass wedge disc



Gate Valve

Forged brass, non-rising stem, heavy duty

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
100-503NL	1/2	SWT x SWT	10	100	0.46	17.98
100-504NL	3/4	SWT x SWT	5	60	0.66	26.62
100-505NL	1	SWT x SWT	5	40	0.99	38.49
100-506NL	1-1/4	SWT x SWT	5	30	1.51	59.03
100-507NL	1-1/2	SWT x SWT	4	24	1.89	73.21
100-508NL	2	SWT x SWT	2	16	2.97	123.11

Features:

- 200 PSI WOG / 125 PSI WSP
- Full port for maximum flow rate
- Non-rising stem for limited-space operation
- Six point cast-iron handle
- Forged brass construction for quality and dependability
- Brass wedge disc



PLUMBING VALVES • LOW PRESSURE • GATE VALVES



Gate Valve

Forged brass, compact pattern

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
100-403NL	1/2	SWT x SWT	-	15	0.42	18.67
100-404NL	3/4	SWT x SWT	-	10	0.66	23.93
100-405NL	1	SWT x SWT	-	5	0.94	33.61
100-406NL	1-1/4	SWT x SWT	-	4	1.47	55.11
100-407NL	1-1/2	SWT x SWT	-	4	1.75	68.30
100-408HC	2	SWT x SWT	-	4	2.71	90.85

Features:

- 200 PSI WOG / 125 PSI WSP
- Standard port
- Non-rising stem for limited-space operation
- Six point cast-iron handle
- Forged brass construction for quality and dependability
- Brass wedge disc



Gate Valve

Forged brass, compact pattern

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
100-453NL	1/2	SWT x SWT	-	15	0.48	18.66
100-454NL	3/4	SWT x SWT	-	10	0.61	23.95
100-455NL	1	SWT x SWT	-	4	0.93	33.61

Features:

- 200 PSI WOG / 125 PSI WSP
- Standard port
- Non-rising stem for limited-space operation
- Six point cast-iron handle
- Forged brass construction for quality and dependability
- Brass wedge disc



Gate Valve

Forged brass, compression

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
100-803NL	1/2	OD x OD	6	48	0.70	40.90
100-804NL	3/4	OD x OD	4	32	1.08	67.23

Features:

- 200 PSI WOG / 125 PSI WSP
- Non-rising stem for limited-space operation
- Six point cast-iron handle
- Forged brass construction for quality and dependability
- Compression ends for solderless connection to copper tubing



PLUMBING VALVES • LOW PRESSURE • STOP VALVES



Stop Valve

Brass

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
105-003NL	1/2	FIP x FIP	-	20	0.55	23.40
105-004NL	3/4	FIP x FIP	-	16	0.60	28.00

Features:

- 125 PSI WOG
- Six-point cast-iron handle
- Rising stem for positive open and close operation



Stop Valve

Brass

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
105-503NL	1/2	SWT x SWT	-	16	0.45	23.40
105-504NL	3/4	SWT x SWT	-	16	0.60	28.00

Features:

- 125 PSI WOG
- Six-point cast-iron handle
- Rising stem for positive open and close operation



Globe Valve

Brass, hard seat

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
106-001NL	1/4	FIP x FIP	10	100	0.50	28.72
106-002NL	3/8	FIP x FIP	10	100	0.57	30.28
106-003NL	1/2	FIP x FIP	10	100	0.57	33.02
106-004NL	3/4	FIP x FIP	5	60	0.75	41.58
106-005NL	1	FIP x FIP	5	40	1.12	65.96
106-006NL	1-1/4	FIP x FIP	5	30	1.94	107.95
106-007NL	1-1/2	FIP x FIP	4	24	2.38	136.07

Features:

- 200 PSI WOG /125 PSI WSP
- Heavy six-point cast-iron handle
- Rising stem for positive open and close operation
- Large flow area



Stop & Waste Valve

Brass

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
105-103NL	1/2	FIP x FIP	-	20	0.50	25.74
105-104NL	3/4	FIP x FIP	-	16	0.55	30.80

Features:

- 125 PSI WOG
- Six-point cast-iron handle
- Rising stem for positive open and close operation
- Plug allows draining of nonpressure side of valve when closed



Stop & Waste Valve

Brass

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
105-603NL	1/2	SWT x SWT	-	16	0.50	25.74
105-604NL	3/4	SWT x SWT	-	16	0.59	30.80

Features:

- 125 PSI WOG
- Six-point cast-iron handle
- Rising stem for positive open and close operation
- Plug allows draining of nonpressure side of valve when closed



Stop & Waste Valve

Brass, compression

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
105-613NL	1/2	OD x OD	-	16	0.65	33.09
105-614NL	3/4	OD x OD	6	36	0.84	38.59

Features:

- 125 PSI WOG
- Compression ends for solderless connection to copper tubing
- Rising stem for positive open and close operation
- Six-point cast-iron handle
- Plug allows draining of nonpressure side of valve when closed



PLUMBING VALVES • LOW PRESSURE • STOP VALVES / CHECK VALVES



Drain Caps

Repair parts, multi-pack

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
888-221RP	3 multi-size pack	FPT	10	80	0.04	4.29

Features:

- Fits most domestic and imported drainable valves
- Cap sizes: 5/16" - 24, 3/8" - 24 & 3/8" - 27

PLUMBING VALVES • LOW PRESSURE • CHECK VALVES



Swing Check Valve

Brass, hard seat, threaded

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
101-002NL	3/8	FIP x FIP	10	100	0.40	15.56
101-003NL	1/2	FIP x FIP	-	15	0.40	19.37
101-004NL	3/4	FIP x FIP	-	15	0.53	28.04
101-005NL	1	FIP x FIP	5	40	0.73	40.08
101-006NL	1-1/4	FIP x FIP	5	30	1.28	68.66
101-007NL	1-1/2	FIP x FIP	4	24	1.70	89.05
101-008NL	2	FIP x FIP	2	16	2.62	132.39

Features:

- 200 PSI WOA



Swing Check Valve

Brass, hard seat, solder

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
101-503NL	1/2	C x C	-	20	0.40	19.36
101-504NL	3/4	C x C	-	20	0.55	28.04
101-505NL	1	C x C	5	40	0.75	40.08
101-506NL	1-1/4	C x C	5	30	1.28	65.32
101-507NL	1-1/2	C x C	4	24	1.52	85.62
101-508NL	2	C x C	2	16	2.56	132.38

Features:

- 200 PSI WOA



In-Line Check Valve

Brass, threaded

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
101-303NL	1/2	FIP x FIP	-	72	0.60	37.62
101-304NL	3/4	FIP x FIP	-	48	0.75	53.36
101-305NL	1	FIP x FIP	-	36	0.97	62.51
101-306NL	1-1/4	FIP x FIP	-	24	1.39	99.84
101-307NL	1-1/2	FIP x FIP	-	15	1.74	118.42
101-308NL	2	FIP x FIP	2	20	2.48	199.51

Features:

- Rated for 200 PSI
- Spring-loaded poppet
- Stainless steel spring for corrosion resistance and long life
- O-ring
- Horizontal or vertical installation capabilities




Swing Check Valve

Brass, hard seat, solder

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
101-343NL	1/2	C x C	10	100	0.27	38.72
101-344NL	3/4	C x C	10	80	0.40	54.93
101-345NL	1	C x C	6	60	0.58	64.38
101-346NL	1-1/4	C x C	4	40	0.95	90.29
101-347NL	1-1/2	C x C	3	30	1.41	121.95
101-348NL	2	C x C	2	20	1.90	206.29

Features:

- 200 PSI Non-shock WOG
- Heavy brass forged construction
- Stainless steel spring
- Metal disc



PLUMBING VALVES • LOW PRESSURE • CHECK VALVES



In-Line Check Valve

PVC, Schedule 40, threaded

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
101-103	1/2	FIP x FIP	10	120	0.28	12.37
101-104	3/4	FIP x FIP	10	120	0.27	13.99
101-105	1	FIP x FIP	8	80	0.50	14.73
101-106	1-1/4	FIP x FIP	6	60	0.90	21.21
101-107	1-1/2	FIP x FIP	6	60	0.89	22.48
101-108	2	FIP x FIP	4	32	1.28	30.42

Features:

- Rated for 200 PSI @ 73°F
- Fits both schedule 40 and 80 pipe
- Spring loaded poppet
- Stainless steel spring for corrosion resistance and longer life
- O-ring seal
- Not for use with compressed air



In-Line Check Valve

PVC, Schedule 40, solvent

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
101-603	1/2	SLIP x SLIP	10	120	0.28	12.37
101-604	3/4	SLIP x SLIP	10	120	0.27	13.99
101-605	1	SLIP x SLIP	8	80	0.50	14.73
101-606	1-1/4	SLIP x SLIP	6	60	0.90	21.21
101-607	1-1/2	SLIP x SLIP	6	60	0.89	22.48
101-608	2	SLIP x SLIP	4	32	1.28	30.42

Features:

- Rated for 200 PSI @ 73°F
- Fits both schedule 40 and 80 pipe
- Spring loaded poppet
- Stainless steel spring for corrosion resistance and longer life
- O-ring seal
- Not for use with compressed air



Dual Check Valve

Brass, backflow preventer, threaded

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
101-404	3/4	FIP x FIP	-	25	1.02	100.96

Features:

- Pressure range from 25 PSI to 175 PSI
- Temperature range -30°F to 140°F
- Prevents the backflow of water
- Stainless steel springs for corrosion resistance and longer life



PLUMBING VALVES • HOSE END VALVES • BOILER DRAIN VALVES



Boiler Drain

Brass, heavy duty

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
102-703	1/2	MIP or SWT	12	72	0.55	14.96
102-704	1/2	MIP or FIP	12	72	0.55	15.98

Features:

- Heavy construction for strength and durability
- Rising stem for positive open and close operation
- For use with hydronic heating systems
- Stuffing box
- Neoprene seal washer
- 3/4" hose thread outlet
- Heavy six-point cast-iron handle



Boiler Drain

Brass, heavy duty

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
102-803	1/2	FIP	12	72	0.55	15.70
102-804	3/4	FIP	12	72	0.55	16.77

Features:

- Heavy construction for strength and durability
- Rising stem for positive open and close operation
- For use with hydronic heating systems
- Stuffing box
- Neoprene seal washer
- 3/4" hose thread outlet
- Heavy six-point cast-iron handle



Boiler Drain

Brass, standard

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
102-003	1/2	MIP	12	72	0.35	12.43
102-003NL	1/2	MIP	12	72	0.35	15.63
102-004	3/4	MIP	12	72	0.45	14.03
102-004NL	3/4	MIP	12	72	0.45	17.46

Features:

- 125 PSI maximum working pressure
- Rising stem for positive open and close operation
- Six-point cast-iron handle
- 3/4" hose thread outlet
- 102-003NL & 102-004NL are Lead Free



Boiler Drain

Brass, standard

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
102-103	1/2	FIP	12	72	0.40	12.82
102-103NL	1/2	FIP	12	72	0.40	17.88
102-104	3/4	FIP	12	72	0.45	14.43
102-104NL	3/4	FIP	12	72	0.45	18.27

Features:

- 125 PSI maximum working pressure
- Rising stem for positive open and close operation
- Six-point cast-iron handle
- 3/4" hose thread outlet
- 102-103NL & 102-104NL are Lead Free



Boiler Drain

Brass, quarter turn, Quarter Master®

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
102-053HN	1/2	MIP or SWT	-	20	0.32	10.92
102-054HN	3/4	MIP or FIP	-	15	0.36	11.84

Features:

- 125 PSI maximum working pressure
- Easy quarter-turn operation
- CSA certified
- Chrome-plated brass ball
- PTFE seats
- Rust-resistant handle
- 3/4" hose thread outlet



Boiler Drain

Brass

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
102-903	1/2	MIP	12	72	0.50	16.05

Features:

- 125 PSI maximum working pressure
- Rising stem for positive open and close operation
- Six point cast-iron handle
- Heavy brass construction for strength and durability
- 3/4" hose thread outlet
- 102-903A: chambered inlet



Water Heater Drain Valve

Brass

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
102-816	1-1/4	MIP	12	72	0.36	15.59
102-817	2-1/4	MIP	12	72	0.43	20.80

Features:

- 125 PSI maximum working pressure
- Heavy brass body for strength and durability
- 3/4" hose thread outlet
- Plated steel canopy handle

GATE VALVES • BRASS



Washing Machine Valve

Chrome-plated brass, front operated

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
102-203	1/2	FIP	12	72	0.33	15.90

Features:

- Chrome-plated brass construction
- Tee handle
- 3/4" hose thread outlet



Washing Machine Valve

Chrome-plated brass, top operated

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
102-202	1/2	FIP	12	72	0.40	19.74

Features:

- Chrome-plated brass construction
- Tee handle
- 3/4" hose thread outlet



Dual Washing Machine Valve

Chrome-plated brass, front operated

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
102-209 - Red	1/2	MIP x MHT	10	60	0.490	24.62
102-210 - Blue	1/2	MIP x MHT	10	60	0.490	24.62

Features:

- Chrome-plated brass construction
- Easy quarter-turn operation
- 3/4" hose threads

PLUMBING VALVES • HOSE END VALVES • HOSE BIBS



Hose Bib

Brass, heavy duty

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
103-013	1/2	MIP or SWT	12	72	0.52	21.09
103-014	3/4	MIP	12	72	0.57	22.10

Features:

- 125 PSI maximum working pressure
- Heavy brass construction for strength and durability
- Neoprene seal washer
- 3/4" hose thread outlet
- High flow rate capacity
- NSF 61 Compliant



Hose Bib

Brass, quarter turn

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
103-053HN	1/2	MIP or SWT	-	20	0.41	16.63
103-054HN	3/4 or 1/2	MIP or FIP	-	15	0.47	18.27

Features:

- 125 PSI maximum working pressure
- Easy quarter-turn operation
- Chrome-plated brass ball
- PTFE seats
- Rust-resistant handle
- 3/4" hose thread outlet



Hose Bib

Forged brass, standard

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
103-003	1/2	MIP	12	72	0.37	12.46
103-004	3/4	MIP	12	72	0.41	14.07

Features:

- 125 PSI maximum working pressure
- 3/4" hose thread outlet
- 103-003NL & 103-004NL are Lead Free



Hose Bib

Forged brass, ball valve type, quarter turn

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
103-023	1/2	MIP or SWT	10	100	0.40	17.27
103-024	3/4	MIP	10	100	0.55	28.25

Features:

- Rated for 200 PSI WOG
- Chrome plated brass ball
- 3/4" hose thread outlet
- High flow rate capacity



No Kink Hose Bib

Brass

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
102-303	1/2	MIP	12	72	0.32	13.49
102-304	3/4	MIP	12	72	0.45	14.60

Features:

- For use with water or oil
- Multi-turn operation
- 3/4" hose thread outlet
- Large flow area
- NSF 61 Compliant



No Kink Hose Bib

Brass

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
102-403	1/2	FIP	12	72	0.36	13.10
102-404	3/4	FIP	12	72	0.36	14.39

Features:

- For use with water or oil
- Multi-turn operation
- 3/4" hose thread outlet
- Large flow area
- NSF 61 Compliant



No Kink Hose Bib

Brass

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
102-534	1/2 or 3/4	SWT	12	72	0.40	14.56

Features:

- For use with water or oil
- Multi-turn operation
- 3/4" hose thread outlet
- Large flow area
- NSF 61 Compliant



No Kink Hose Bib

Brass, Quarter Master®

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
102-353HN	1/2	MIP	-	12	0.41	16.47
102-354HN	3/4	MIP	-	12	0.46	16.91
102-453HN	1/2	FIP	-	12	0.35	15.56
102-454HN	3/4	FIP	-	12	0.38	16.36

Features:

- 125 PSI maximum working pressure
- Easy quarter-turn operation
- Chrome plated brass ball
- PTFE seats
- Rust-resistant handle
- 3/4" hose thread outlet





Sillcock

Brass, heavy duty with Lockshield

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
108-013	1/2	FIP	12	72	0.80	26.44
108-014	3/4	FIP	12	72	0.75	27.12

Features:

- 125 PSI maximum working pressure
- Lockshield prevents unwanted use of valve when handle is removed
- 3/4" hose thread outlet
- Heavy construction for strength & durability
- Oversized notched flange for stable installation



Sillcock

Brass

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
108-503	1/2 or 3/4	SWT	12	72	0.55	18.10

Features:

- 125 PSI maximum working pressure
- Heavy construction for strength and durability
- Six-point cast-iron handle
- 3/4" hose thread outlet
- Oversized notched flange for stable installation
- NSF 61 Compliant



Garden Valve

Brass, bent nose design

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
108-103	1/2	FIP	12	72	0.70	19.83
108-104	3/4	FIP	12	72	0.70	22.03
108-105	1	FIP	12	72	0.75	23.81

Features:

- Female threaded inlet
- Large full flow area
- 3/4" hose thread outlet
- Cast iron handle
- NSF 61 Compliant



Frost Free Sillcock

Chrome-plated brass, 1/2" male & 1/2" solder, multi-turn

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
104-401	1/2 x 4	MIP or SWT	-	24	0.80	50.95
104-402	1/2 x 6	MIP or SWT	-	24	0.87	51.01

Features:

- Chrome-plated brass body and tube for corrosion resistance
- 3/4" hose thread outlet
- Heavy-duty six-point cast-iron handle
- Automatically drains upon water shutoff
- Notched flange allows stable installation on siding
- NSF 61 Compliant



Sillcock

Brass

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
108-003	1/2	FIP	12	72	0.50	14.70
108-004	3/4	FIP	12	72	0.50	16.10

Features:

- 125 PSI maximum working pressure
- Heavy construction for strength and durability
- Six-point cast-iron handle
- 3/4" hose thread outlet
- Oversized notched flange for stable installation
- 108-003 & 108-004 are NSF 61 Compliant
- 108-003NL & 108-004NL are NSF 61 Compliant



Sillcock

Brass, quarter turn

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
108-053HN	1/2	FIP	-	15	0.37	12.55
108-054HN	3/4	FIP	-	12	0.40	13.28
108-553HN	3/4 or 1/2	FIP or SWT	-	15	0.46	13.28

Features:

- 125 PSI maximum working pressure
- Easy quarter-turn operation
- Chrome-plated brass ball
- 3/4" hose thread outlet



Anti-Siphon Frost Free Sillcock

Chrome-plated brass, 1/2" male & 1/2" solder, multi-turn, anti-siphon

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
104-513HC	1/2	MIP or SWT	-	8	1.41	60.05
104-515HC	3/4	MIP or SWT	-	10	1.53	62.21
104-517HC	1	MIP or SWT	-	10	1.66	63.72
104-519HC	2	MIP or SWT	-	10	1.76	67.64
104-521HC	3	MIP or SWT	-	5	1.63	69.87

Features:

- Chrome-plated brass body and tube for corrosion resistance
- Constructed with lead-free silver solder
- Built-in lockshield
- 3/4" hose thread outlet
- Heavy-duty six-point cast-iron handle
- Notched flange for stable installation
- Backflow preventer checks siphoning back into the water supply
- Automatically drains upon water shutoff
- NSF 61 Compliant





Stem Cartridge Kit

QuarterMaster® quarter turn anti-siphon replacement stem

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
889-558	8"	-	1	20	0.32	36.08

Features:

- Replacement stem for item 104-519



Vaccum Breaker

Brass, backflow preventer

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
108-904	3/4	FIP	6	72	0.20	10.05
108-904NL	3/4	FIP	6	72	0.20	13.20

Features:

- 125 PSI maximum working pressure
- Heavy construction for strength and durability
- Six-point cast-iron handle
- 3/4" hose thread outlet
- Oversized notched flange for stable installation
- 108-904NL is Lead Free
- NSF 61 Compliant



Meter Coupling

Brass

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
105-783NL	1/2	MIP x FIP	10	100	0.30	16.95
105-784NL	3/4	MIP x FIP	10	100	0.35	24.73
105-785NL	1	MIP x FIP	10	100	0.60	29.16

Features:

- Flare nut included
- Neoprene seal washer
- Large flow area
- Heavy six-point cast-iron handle



Radiator Valve

Brass

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
109-303	1/2	FIP x MIP	6	60	0.79	42.37
109-304	3/4	FIP x MIP	6	48	1.12	55.90
109-305	1	FIP x MIP	6	36	1.52	73.40
109-306	1-1/4	FIP x MIP	6	24	2.07	105.00
109-307	1-1/2	FIP x MIP	2	16	3.17	132.00

Features:

- 60 PSI non-shock hot water
- 15 PSI working steam pressure
- For low-pressure steam or circulated hot water
- Adjustable packing
- Rising stem
- Heat-resistant poly handle