



**7700 SERIES  
BRASS FULL PORT BALL VALVES**

**BV 0822**  
Effective Aug 22, 2022

The issuance of this price list is not an offer to sell the goods listed herein at the prices stated.



**SERIES 7700T  
Lead Free  
Brass Ball Valve**

Threaded with packing gland



**SERIES 7700TT  
Lead Free  
Brass Ball Valve**

Threaded with 'T-Handle' and packing gland

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
117-821	1/4	FIP x FIP	15	60	0.30	9.85
117-822	3/8	FIP x FIP	15	60	0.31	10.08
117-823	1/2	FIP x FIP	15	60	0.45	12.46
117-824	3/4	FIP x FIP	10	60	0.77	20.21
117-825	1	FIP x FIP	6	24	1.14	30.95
117-826	1-1/4	FIP x FIP	4	16	1.78	52.72
117-827	1-1/2	FIP x FIP	2	24	2.31	75.93
117-828	2	FIP x FIP	2	12	3.58	110.64
117-829	2-1/2	FIP x FIP	2	6	7.24	247.73
117-830	3	FIP x FIP	2	4	10.03	332.37
117-831	4	FIP x FIP	1	2	19.29	593.52

**Features:**

- 600PSI/150 WSP (1/2"-2")
- 400PSI Non-Shock WOG (2-1/2" - 4")
- -20°F to 300°F temperature range
- Full port for maximum flow rate
- Packing Gland - blowout proof stem design
- PTFE seat & packing
- Rust-resistant heavy-duty handle



Item	Size	Connection	Inner Qty	Master Qty	Weight	List
117-823T	1/2	FIP x FIP	15	60	0.45	\$14.23
117-824T	3/4	FIP x FIP	10	60	0.77	\$23.82
117-825T	1	FIP x FIP	6	24	1.14	\$37.13

**Features:**

- 600PSI/150 WSP (1/2" - 2")
- -20°F to 300°F temperature range
- Full port for maximum flow rate
- Packing Gland - blowout proof stem design
- PTFE seat & packing
- Chrome-plated brass ball & stem
- Stainless T-Handle



**SERIES 7700TW  
Lead Free  
Brass Ball Valve**

Threaded, stop & waste with packing gland



Item	Size	Connection	Inner Qty	Master Qty	Weight	List
117-753	1/2	FIP x FIP	15	60	0.50	\$14.77
117-754	3/4	FIP x FIP	10	60	0.80	\$23.62
117-755	1	FIP x FIP	6	24	1.18	\$36.17

**Features:**

- 600PSI/150 WSP (1/2"-2")
- -20°F to 300°F temperature range
- Full port for maximum flow rate
- Packing Gland - blowout-proof stem design
- PTFE seat & packing
- Drain port
- Rust-resistant heavy-duty handle with vinyl grip



**SERIES 7700S  
Lead Free  
Brass Ball Valve**

Solder with packing gland

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
117-843	1/2	SWT x SWT	15	60	0.40	\$11.34
117-844	3/4	SWT x SWT	10	60	0.69	\$19.43
117-845	1	SWT x SWT	6	24	1.05	\$30.63
117-846	1-1/4	SWT x SWT	4	16	1.61	\$54.14
117-847	1-1/2	SWT x SWT	2	24	2.23	\$75.71
117-848	2	SWT x SWT	2	12	3.58	\$116.52
117-849	2-1/2	SWT x SWT	2	6	6.77	\$240.02
117-850	3	SWT x SWT	2	4	9.41	\$315.75
117-851	4	SWT x SWT	1	2	18.70	\$585.69

**Features:**

- 600PSI/150 WSP (1/2"-2")
- 400PSI Non-Shock WOG (2-1/2" - 4")
- -20°F to 300°F temperature range
- Full port for maximum flow rate
- Packing Gland - blowout-proof stem design
- PTFE seat & packing
- Rust-resistant heavy-duty handle with vinyl grip





## SERIES 7700SW

### Lead Free Brass Ball Valve

Solder stop & waste with packing gland

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
117-553	1/2	SWT x SWT	15	60	0.43	\$13.68
117-554	3/4	SWT x SWT	10	60	0.73	\$19.37
117-555	1	SWT x SWT	6	24	1.07	\$34.62

#### Features:

- 600PSI/150 WSP (1/2"-2")
- -20°F to 300°F temperature range
- Full port for maximum flow rate
- Packing Gland - blowout-proof stem design
- PTFE seat & packing
- Drain port
- Rust-resistant heavy-duty handle with vinyl grip



## SERIES 7700TH

### Lead Free Brass Ball Valve

Threaded with Hose Chain and Packing Gland

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
117-923	1/2	FIP x HOSE	10	100	0.61	23.00
117-924	3/4	FIP x HOSE	10	60	0.89	30.00
117-925	1	FIP x HOSE	6	36	1.28	56.00

#### Features:

- 600PSI/150 WSP (1/2"-2")
- -20°F to 200°F temperature range
- Full port for maximum flow rate
- Packing Gland - blowout-proof stem design
- PTFE seat & packing
- Hose end connection
- Rust-resistant heavy-duty handle with vinyl grip



## SERIES 7700SH

### Lead Free Brass Ball Valve

Solder with Hose Chain and Packing Gland

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
117-943	1/2	SWT x HOSE	10	100	0.57	21.00
117-944	3/4	SWT x HOSE	10	60	0.83	28.00
117-945	1	SWT x HOSE	6	36	1.21	52.00

#### Features:

- 600PSI/150 WSP (1/2"-2")
- -20°F to 200°F temperature range
- Full port for maximum flow rate
- Packing Gland - blowout-proof stem design
- PTFE seat & packing
- Hose end connection
- Rust-resistant heavy-duty handle with vinyl grip



## SERIES 7700PX

### Lead Free Brass Ball Valve

F1807 PEX with packing gland

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
117-343	1/2	F1807 PEX x F1807 PEX	10	120	0.27	\$8.74
117-344	3/4	F1807 PEX x F1807 PEX	10	80	0.41	\$12.92
117-345	1	F1807 PEX x F1807 PEX	6	48	0.67	\$20.09

#### Features:

- 400PSI Non-Shock CWP
- 180°F max temperature
- Full port for maximum flow rate
- Packing Gland - blowout-proof stem design
- PTFE seat & packing
- Rust-resistant heavy-duty handle with vinyl grip



## SERIES 7700EX

### Lead Free Brass Ball Valve

F1960 PEX with packing gland

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
117-353	1/2	F1960 PEX x F1960 PEX	10	100	0.32	\$12.02
117-354	3/4	F1960 PEX x F1960 PEX	10	100	0.49	\$17.13
117-355	1	F1960 PEX x F1960 PEX	8	80	0.83	\$30.25
117-356	1-1/4	F1960 PEX x F1960 PEX	4	36	1.26	\$45.97
117-357	1-1/2	F1960 PEX x F1960 PEX	2	24	1.86	\$67.21
117-358	2	F1960 PEX x F1960 PEX	2	12	2.98	\$116.30

#### Features:

- 400PSI Non-Shock CWP
- 180°F max temperature
- Full port for maximum flow rate
- Packing Gland - blowout-proof stem design
- PTFE seat & packing
- Rust-resistant heavy-duty handle with vinyl grip



## SERIES 7700SE

### Handle Extension

Valve handle extension

Item	Size	Connection	Inner Qty	Master Qty	Weight	List
889-823	1/2 - 3/4	-	-	50	0.16	\$10.23
889-825	1 - 1-1/4	-	-	50	0.19	\$13.18
889-827	1-1/2 - 2	-	-	50	0.22	\$16.20
889-829	2-1/2 - 4	-	-	40	0.47	\$18.30

#### Features:

- For 7700 ball valve series